



Smartbright Pro Downlight

DN068B LED26/865 PSU GM

Smartbright Pro Downlight, 24 W, 2650 lm, 6500 K, Matte, IP20 | Finger-protected

The SmartBright Pro Downlight comes offering reliable lighting performance with recessed installation, suitable for diversified applications. Full wattage ranges from 5W to 24W, full CCT range covering 3000K, 3500K, 4000K and 6500K, eye comfort experience with low flicker lighting can attract you more with its elegant design.

Product data

General Information	
Light source engine type	LED
Power Factor (Fraction) 0.5	
Number of products on MCB of 16 A type B 20	
Light Technical	
Luminous Flux	2,650 lm
Luminous Efficacy (rated) (Nom)	110 lm/W
Correlated Color Temperature (Nom)	6500 K
Color rendering index (CRI)	>80
Light source color	865 cool daylight
Optical cover type	Polycarbonate Diffuser
Temperature	
Ambient temperature range	-20 to +40 °C
Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	White
Optical cover finish	Matte
Overall height	45 mm

Smartbright Pro Downlight

Overall diameter	220 mm
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class II
Flammability mark	For mounting on normally flammable surfaces
CE mark	-
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+10%/-15%
Initial chromaticity	(0.31, 0.34) SDCM <7
Power consumption tolerance	+/-10%

Product Data	
Order product name	DN068B LED26/865 PSU GM
Full product name	DN068B LED26/865 PSU GM
Full product code	871951495782499
Order code	911401873184
Material Nr. (12NC)	911401873184
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.053 kg
EAN/UPC - Product/Case	8719514957824
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514958067

Dimensional drawing

