



# Smartbright Pro Downlight

## DN068B LED9/840 PSU GM

Smartbright Pro Downlight, 9 W, 900 lm, 4000 K, Matte, IP20 | Finger-protected

The SmartBright Pro Downlight comes offering reliable lighting performance with recessed installation, suitable for diversified applications. Full wattage ranges from 5W to 24W, full CCT range covering 3000K, 3500K, 4000K and 6500K, eye comfort experience with low flicker lighting can attract you more with its elegant design.

### Product data


General Information	
Light source engine type	LED
Power Factor (Fraction) 0.5	
Number of products on MCB of 16 A type B 21	
Light Technical	
Luminous Flux	900 lm
Luminous Efficacy (rated) (Nom)	102 lm/W
Correlated Color Temperature (Nom)	4000 K
Color rendering index (CRI)	>80
Light source color	840 neutral white
Optical cover type	Polycarbonate Diffuser
Ambient temperature range -20 to +40 °C	
Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	White
Optical cover finish	Matte
Overall height	45 mm
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	10 A
Power Consumption	9 W

# Smartbright Pro Downlight

Overall diameter	125 mm
<b>Approval and Application</b>	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class II
Flammability mark	For mounting on normally flammable surfaces
CE mark	-
<b>Initial Performance (IEC Compliant)</b>	
Luminous flux tolerance	+10%/-15%
Initial chromaticity	(0.38, 0.38) SDCM <7
Power consumption tolerance	+/-10%

<b>Product Data</b>	
Order product name	DN068B LED9/840 PSU GM
Full product name	DN068B LED9/840 PSU GM
Full product code	871951495765799
Order code	911401871484
Material Nr. (12NC)	911401871484
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.080 kg
EAN/UPC - Product/Case	8719514957657
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514957893

## Dimensional drawing



DN068B 9W D105

