



Smartbright Pro Downlight

DN068B LED9/865 PSU GM

Smartbright Pro Downlight, 9 W, 900 lm, 6500 K, Matte, IP20 | Finger-protected

The SmartBright Pro Downlight comes offering reliable lighting performance with recessed installation, suitable for diversified applications. Full wattage ranges from 5W to 24W, full CCT range covering 3000K, 3500K, 4000K and 6500K, eye comfort experience with low flicker lighting can attract you more with its elegant design.

Product data

General Information		Power Factor (Fraction)		0.5
Light source engine type	LED	Number of products on MCB of 16 A type B		21
Light Technical		Temperature		
Luminous Flux	900 lm	Ambient temperature range	-20 to +40 °C	
Luminous Efficacy (rated) (Nom)	102 lm/W	Controls and Dimming		
Correlated Color Temperature (Nom)	6500 K	Dimmable	No	
Color rendering index (CRI)	>80	Control interface	-	
Light source color	865 cool daylight	Mechanical and Housing		
Optical cover type	Polycarbonate Diffuser	Housing Material	Polycarbonate	
Operating and Electrical		Optical cover material	Polycarbonate	
Input Voltage	220 to 240 V	Housing Color	White	
Line Frequency	50 or 60 Hz	Optical cover finish	Matte	
Inrush current	10 A	Overall height	45 mm	
Power Consumption	9 W			

Smartbright Pro Downlight

Overall diameter	125 mm
------------------	--------

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Protection class IEC	Safety class II
Flammability mark	For mounting on normally flammable surfaces
CE mark	-


Initial Performance (IEC Compliant)

Luminous flux tolerance	+10%/-15%
Initial chromaticity	(0.31, 0.34) SDCM <7
Power consumption tolerance	+/-10%

Product Data

Order product name	DN068B LED9/865 PSU GM
Full product name	DN068B LED9/865 PSU GM
Full product code	871951495766499
Order code	911401871584
Material Nr. (12NC)	911401871584
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.019 kg
EAN/UPC - Product/Case	8719514957664
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514957909

Dimensional drawing



DN068B 9W D105

