



GreenPerform ultra efficient panel RC199B

RC199V LED38/840 PSD W60L60 CAU UE

GreenPerform ultra efficient panel RC199B, 165 lm/W, 840 neutral white, DALI

GreenPerform ultra efficient panel is a direct lit panel with up to 170lm/w system efficacy (PSU driver) in the market. It offers 3 typical dimensions: 600x600; 300x1200 and 600x1200mm to fit most of indoor applications. Interact system option and Dali interface are available for wide option for system connection. Its lower UGR offers better visual comfort as well.

Product data

| General Information | | Optic type | |
|------------------------------------|-------------------|--------------------------|--------------|
| Number of gear units | 1 unit | Optical cover type | PS |
| Gear | - | Unified glare rating CEN | 22 |
| Driver included | Yes | Operating and Electrical | |
| Light source engine type | LED | Input Voltage | 200 to 240 V |
| Light Technical | | Line Frequency | 50 to 60 Hz |
| Luminous Flux | 3,800 lm | Inrush current | 36 A |
| Luminous Efficacy (rated) (Nom) | 165 lm/W | Inrush time | 210 ms |
| Correlated Color Temperature (Nom) | 4000 K | Power Consumption | 23 W |
| Color rendering index (CRI) | 80 | Power Factor (Fraction) | 0.9 |
| Number of light sources | 96 | Connection | - |
| Light source color | 840 neutral white | | |

GreenPerform ultra efficient panel RC199B

| | |
|---|---|
| Number of products on MCB of 16 A type B 16 | |
| Temperature | |
| Ambient temperature range | -20 to +45 °C |
| Controls and Dimming | |
| Dimmable | DALI |
| Control interface | DALI |
| Mechanical and Housing | |
| Housing Material | Aluminum extruded |
| Optic material | Polystyrene |
| Optical cover material | Polystyrene |
| Housing Color | White RAL 9003 |
| Mounting device | - |
| Optical cover finish | Diamond |
| Overall length | 595 mm |
| Overall width | 595 mm |
| Overall height | 34 mm |
| Overall diameter | 595 mm |
| Dimensions (Height x Width x Depth) | 34 x 595 x 595 mm |
| Approval and Application | |
| Ingress protection code | IP20/40 [Finger-protected,Wire-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Protection class IEC | Safety class II |
| Glow-wire test | Temperature 650 °C, duration 30 s |

| | |
|----------------------|--|
| Flammability mark | - |
| CE mark | CE mark |
| ENEC mark | - |
| Warranty period | 3 years |
| Photobiological risk | Photobiological risk group 0 @200mm to EN62778 |
| EU RoHS compliant | Yes |

Initial Performance (IEC Compliant)

| | |
|-----------------------------|--------|
| Luminous flux tolerance | +/-10% |
| Power consumption tolerance | +/-10% |


Application Conditions

| | |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C |
| Maximum dim level | 0% (digital) |
| Suitable for random switching | Not applicable |

Product Data

| | |
|---------------------------------|------------------------------------|
| Order product name | RC199V LED38/840 PSD W60L60 CAU UE |
| Full product name | RC199V LED38/840 PSD W60L60 CAU UE |
| Order code | 911401549444 |
| Material Nr. (12NC) | 911401549444 |
| Numerator - Quantity Per Pack | 1 |
| Net Weight (Piece) | 1.600 kg |
| Numerator - Packs per outer box | 4 |

Dimensional drawing



GreenPerform ultra efficient panel RC199B

