



GreenPerform ultra efficient panel RC199B

RC199X LED38/840 WIA W60L60 CAU UE

GreenPerform ultra efficient panel RC199B, 170 lm/W, 840 neutral white, InterAct Pro

GreenPerform ultra efficient panel is a direct lit panel with up to 170lm/w system efficacy (PSU driver) in the market. It offers 3 typical dimensions: 600x600; 300x1200 and 600x1200mm to fit most of indoor applications. Interact system option and Dali interface are available for wide option for system connection. Its lower UGR offers better visual comfort as well.

Product data

General Information		Optic type	
Number of gear units	1 unit	Optical cover type	PS
Gear	-	Unified glare rating CEN	22
Driver included	Yes	Operating and Electrical	
Light source engine type	LED	Input Voltage	200 to 240 V
Light Technical		Line Frequency	50 to 60 Hz
Luminous Flux	3,800 lm	Inrush current	36 A
Luminous Efficacy (rated) (Nom)	170 lm/W	Inrush time	210 ms
Correlated Color Temperature (Nom)	4000 K	Power Consumption	22 W
Color rendering index (CRI)	80	Power Factor (Fraction)	0.9
Number of light sources	96	Connection	-
Light source color	840 neutral white		

GreenPerform ultra efficient panel RC199B

Number of products on MCB of 16 A type B 16	
Temperature	
Ambient temperature range	-20 to +45 °C
Controls and Dimming	
Dimmable	Wireless Dim
Control interface	InterAct Pro
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Polystyrene
Optical cover material	Polystyrene
Housing Color	White RAL 9003
Mounting device	-
Optical cover finish	Diamond
Overall length	595 mm
Overall width	595 mm
Overall height	34 mm
Overall diameter	595 mm
Dimensions (Height x Width x Depth)	34 x 595 x 595 mm
Approval and Application	
Ingress protection code	IP20/40 [Finger-protected,Wire-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s

Flammability mark	-
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%


Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	0% (digital)
Suitable for random switching	Not applicable

Product Data

Order product name	RC199X LED38/840 WIA W60L60 CAU UE
Full product name	RC199X LED38/840 WIA W60L60 CAU UE
Order code	911401550044
Material Nr. (12NC)	911401550044
Numerator - Quantity Per Pack	1
Net Weight (Piece)	1.600 kg
Numerator - Packs per outer box	4

Dimensional drawing



GreenPerform ultra efficient panel RC199B

