

**PHILIPS****Lighting**

# PowerBalance G4

## RC650B LED40S965 PSD W60L60

PowerBalance G4, 135.3 lm/W, 965 cool daylight, DALI

PowerBalance G4 (RC650 range) is a complete office lighting family which creates a modern, flexible and comfortable environment that fosters creativity and innovation. It provides multiple control options (Interact office, Interact pro, POE) to make your office energy-efficient and easy to manage.

### Product data

| General Information                |                   | Operating and Electrical                 |                               |
|------------------------------------|-------------------|--|-------------------------------|
| Number of gear units               | 1 unit            | Input Voltage                            | 220 to 240 V                  |
| Driver included                    | Yes               | Line Frequency                           | 50 or 60 Hz                   |
| Light source engine type           | LED               | Initial CLO power consumption            | N.A. W                        |
| Service tag                        | Yes               | Average CLO power consumption            | N.A. W                        |
| Value ladder                       | Specification     | Inrush current                           | 23.1 A                        |
| Warranty period                    | 3 years           | Inrush time                              | 221 ms                        |
| Light Technical                    |                   | Power Consumption                        |                               |
| Luminous Flux                      | 3,950 lm          | Power Factor (Fraction)                  | 0.9                           |
| Correlated Color Temperature (Nom) | 6500 K            | Connection                               | Screw connection block 5-pole |
| Luminous Efficacy (rated) (Nom)    | 135.3 lm/W        | Number of products on MCB of 16 A type B | 22                            |
| Color rendering index (CRI)        | >90               | Suitable for random switching            | No                            |
| Beam angle of light source         | 120 degree(s)     | Protection class IEC                     | Safety class I                |
| Light source color                 | 965 cool daylight | Controls and Dimming                     |                               |
| Optic type                         | Reflector         | Dimmable                                 | Yes                           |
| Luminaire light beam spread        | 100° x 100°       | Driver/power unit/transformer            | Power supply unit (On/Off)    |
| Unified glare rating CEN           | 16                | Control interface                        | DALI                          |
|                                    |                   | Constant light output                    | No                            |

## PowerBalance G4

|  |   |                           |               |
|--|---|---------------------------|---------------|
| Maximum dim level                            | Programmable                                | EU RoHS compliant         | Yes           |
|  |   | Ambient temperature range | -20 to +40 °C |
| <b>Mechanical and Housing</b>                |   |                           |               |
| Housing Material                             | Steel                                       |                           |               |
| Reflector material                           | Polycarbonate                               |                           |               |
| Optic material                               | Polycarbonate                               |                           |               |
| Optical cover material                       | Polycarbonate                               |                           |               |
| Fixation material                            | Steel                                       |                           |               |
| Housing Color                                | White                                       |                           |               |
| Optical cover finish                         | Textured                                    |                           |               |
| Overall length                               | 597 mm                                      |                           |               |
| Overall width                                | 597 mm                                      |                           |               |
| Overall height                               | 70 mm                                       |                           |               |
| Dimensions (Height x Width x Depth)          | 70 x 597 x 597 mm                           |                           |               |
| Ingress protection code                      | IP20 [Finger-protected]                     |                           |               |
| Mech. impact protection code                 | IK03 [0.3 J]                                |                           |               |
| Optical cover type                           | Polycarbonate                               |                           |               |
| Net Weight (Piece)                           | 4.000 kg                                    |                           |               |
| <b>Approval and Application</b>              |   |                           |               |
| Glow-wire test                               | Temperature 650 °C, duration 30 s           |                           |               |
| Flammability mark                            | For mounting on normally flammable surfaces |                           |               |
| CE mark                                      | Yes   |                           |               |
| ENEC mark                                    | -   |                           |               |
| <b>Initial Performance (IEC Compliant)</b>   |   |                           |               |
| Luminous flux tolerance                      | +/-10%                                      |                           |               |
| Initial chromaticity                         | SDCM<3                                      |                           |               |
| Power consumption tolerance                  | +/-10%                                      |                           |               |
| <b>Over Time Performance (IEC Compliant)</b> |   |                           |               |
| Median useful life L70B50                    | 50,000 hour(s)                              |                           |               |
| Median useful life L80B50                    | 50,000 hour(s)                              |                           |               |
| Median useful life L90B50                    | 33,817 hour(s)                              |                           |               |
| <b>Product Data</b>                          |   |                           |               |
| Order product name                           | RC650B LED40S965 PSD W60L60                 |                           |               |
| Full product name                            | RC650B LED40S965 PSD W60L60                 |                           |               |
| Full product code                            | 692234199457999                             |                           |               |
| Order code                                   | 99457999                                    |                           |               |
| Material Nr. (12NC)                          | 911401580161                                |                           |               |
| Numerator - Quantity Per Pack                | 1   |                           |               |
| EAN/UPC - Product/Case                       | 6922341994579                               |                           |               |
| Numerator - Packs per outer box              | 2   |                           |               |
| EAN/UPC - Case                               | 6922341994579                               |                           |               |

### Dimensional drawing

